


## HYDRO50R - HIGH PURITY HYDROGEN GENERATOR MODULE



# H<sub>2</sub>

### APPLICATIONS

- ✓ Combustion gas for FID Analyzers
- ✓ Carrier gas for Gas Chromatographs
- ✓ Protection gas

### DESCRIPTION

Synspec B.V. supplies the **HYDRO50R** product line of **High Purity Hydrogen Generator** modules for FID and CARRIER GAS for GC, to fit almost any type of application which needs H<sub>2</sub> production close to the consumer.

Based on the field proven Solid Polymer Electrolyte (PEM) cell technology, pure Hydrogen is produced at low pressure from electricity and high quality distilled water (ZEROWATER). This process can be started on demand and does not require any caustic solution. The instrument could be alimented directly from a bi-distilled water distribution network. (option)

The produced Hydrogen is available 24/7 with constant purity of **99.999%** at an output flow of **100 Nml/min**. The H<sub>2</sub> output pressure is regulated electronically and can be set from 0.5 to 7 bar.(7 to 102 psig).

Each instrument is equipped with high performance communication interfaces RS485 and USB as standard (Ethernet, WLAN as option) to create a very flexible gas network with local or central control.

Due to the software being focused on safety, automatic regulation and reliable communications, the **HYDRO50R High Purity Hydrogen Generator** modules are easy to install, reliable, safe and pleasant to operate.

### BENEFITS

- ✓ Reduces in operation costs. Return on investment within 2 years.
- ✓ Improves resolution and detection limit versus Helium only usage. Provides High pressure stability.
- ✓ H<sub>2</sub> available 24/7 at constant purity. No contamination.
- ✓ Independent source of Hydrogen that does not require any piping and can be easily moved around the laboratory.
- ✓ Remote control from PC, I-phone and I-pad
- ✓ Very safe operation, internal leak-test, automatic shut-down, over-pressure valve, current and voltage limits.
- ✓ No handling and storage of cumbersome gas cylinders. No cylinder rental fee.
- ✓ Extended autonomy with 5L water tank.

# HIGH PURITY HYDROGEN GENERATOR MODULE

## SPECIFICATIONS

<b>Models</b>	<b>HYDRO50R-100</b>
H2 Outflow @ 1013/20°C	HYDRO50R-100 = 100 Nml/min
H2 purity	<b>&gt;99.999% (HC&lt;0.1ppm)</b>
Dew point	-40°C / -45°F
Outlet Pressure	From 0.5 to 7 bar (7 to 102 psig), adjustable by software.
Water quality	High purity deionized filtered water. TOC free.
Water alimentation	By external 5L tank, or central distribution network (option)
Water consumption	5L water generates about 6000L Hydrogen
Safety	Low H2 stored volume; over pressure valve; internal leak test; automatic shut down; maximum current limit, water quality.
Manual control	ON-OFF power switch
Remote control, Communications	<ul style="list-style-type: none"><li>■ Through 2 potential free relay contacts (I/O),</li><li>■ RS485 (Mod-Bus), USB.</li><li>■ Trough Ethernet 10/100 network (option)</li><li>■ Trough WLAN network, with PC, I-Phone, I-Pad (option)</li><li>■ Log book download by USB.</li></ul>
H2 outlet fitting	Stainless steel 1/8" OD compression
Power supply	Automatic switching from 90VAC to 260VAC, 47 to 63 Hz
Power consumption ( max at full flow)	HYDRO50R-100: maximum 150W
Dimensions	W=220mm/8.1ins, H=130mm/5.1ins, D=350mm/13.8ins
Net weight (Kg/lbs)	HYDRO50R-100: 8 Kg / 18 Lbs
Certification	CE

## ORDERING NUMBERS

<b>Model</b>	<b>Article #</b>
HYDRO50R-100	8086
HYDRO50R with other capacities	on demand

### **SYNSPEC B.V.**

De Deimten 1 – Zernike Science Park

NL – 9747 AV GRONINGEN

Telephone: +31 50 526 64 54

[info@synspec.nl](mailto:info@synspec.nl)

[www.synspec.nl](http://www.synspec.nl)